

ITEMS	AEROLYN 2000	AEROLYN 4000
MODEL NUMBER	AE2000	AE4000
HEATING CAPACITY	0.9 - 2.3 kW	1.0 - 3.5 kW
FUEL CONSUMPTION	0.1 - 0.29 I/H	0.12 - 0.43 I/H
WORKING VOLTAGE	12 / 24V	12 / 24V
POWER CONSUMPTION	4.8 -36 W	6.0 -52.8 W
HEATING AIR FLOW AGAINST 0.5 MBAR	121 m3/H	170 m3/H
WEIGHT	2.7 KG	6.5 KG
OUTLINE DIMENSIONS	12.2" X 4.5" X 4.8"	16.7" X 5.9" X 6.3"
OPERATING AMBIENT TEMPERATURE	-49°F - 131°F	-49°F - 131°F
STORAGE TEMPERATURE	-67°F - 158°F	-67°F - 158°F
WARRANTY	2 YEARS	2 YEARS
		
		
FEATURES		
RAPIDLY HEAT THE CABIN OR SPACE UP TO 565 ft³ WITHOUT IDLING THE ENGINE		
HEAT OUTPUT OF 4kW OR 14,000 BTU/h		
ADAPTIVE FREQUENCY CONTROL TECHNOLOGY TO SAVE FUEL AND REDUCE EMISSIONS		
NORMAL OPERATION AT 16,000 FT ELEVATION AND -40°F		
COMPACT DESIGN AND EASY INSTALLATION		
ALLOY 310S USED FOR COMBUSTION CHAMBER		
BUSHLESS MOTOR		
QUIET OPERATION		
WATER RESISTANT - IPX6		
KYOCERA GLOW PIN		
E-MARK CERTIFIED		

ITEMS	AQUANO 10K
MODEL NUMBER	AQ10000
HEATING CAPACITY	4.4 - 10.3 kW
FUEL CONSUMPTION	0.51 - 1.29 I/H
WORKING VOLTAGE	12 / 24V
POWER CONSUMPTION	74.4 -104.4 W
WEIGHT	7 KG
OUTLINE DIMENSIONS	17.1" X 8.3" X 7.0"
OPERATING AMBIENT TEMPERATURE	-49°F - 131°F
STORAGE TEMPERATURE	-67°F - 158°F
WARRANTY	2 YEARS

